

ELVATECH PRECISION THAT
EMPOWERS CONFIDENCE

PROSPECTOR 2 LE



**ADVANCED XRF ANALYSIS OF ANY
ELEMENTS IN VARIOUS MATERIALS**

PROSPECTOR 2 LE IS AN ADVANCED, VERSATILE XRF ANALYZER DESIGNED FOR HIGH-PRECISION ANALYSIS, CAPABLE OF MEASURING BOTH LIGHT AND HEAVY ELEMENTS

Perfect for specialized tasks in environmental studies, jewelry analysis, and more, this model delivers greater sensitivity and flexibility for a wide range of applications.

SUPERIOR SENSITIVITY FOR LIGHT ELEMENTS

With a large-area SDD detector, ProSpector 2 LE provides high sensitivity for light elements such as magnesium (Mg), aluminum (Al), and silicon (Si), making it perfect for environmental research and other specialized tasks.

AUTOMATED FLEXIBILITY

The 5-position automatic filter changer adapts to various materials, ensuring optimal performance without the need for manual adjustments.

HIGH PRECISION

The ability to precisely localize the analysis area with an optional CCD camera ensures accuracy even in small or intricate samples.

COMPACT AND DURABLE

Designed for portability and reliability, ProSpector 2 LE's compact size (242 × 230 × 78 mm; 1.4 kg) and IP54 protection allow for use in both field and laboratory environments.



TWICE
better precision

TWICE
lower detection limits

FOUR TIMES
faster than other handheld XRF

WIDE DETECTION RANGE

Capable of analyzing elements from magnesium (Mg) to uranium (U), ProSpector 2 LE is perfect for light and heavy element applications.

ADVANCED FILTER

The automatic 5-position filter and fixed collimator enable flexibility in analyzing a wide range of materials and samples.

PRECISION IMAGING

With the optional CCD camera, ProSpector 2 LE allows for precise localization of the analysis area, ensuring high accuracy even for small or complex samples.

INTERACTIVE TOUCHSCREEN

A 4.3" touchscreen ensures easy, intuitive operation and quick data handling.

Cements	
Today, 11:43 AM 1886	
LOI:	1.560 ± 0%
CaO:	68.16 ± 0.16%
SiO ₂ :	21.54 ± 0.20%
Al ₂ O ₃ :	3.83 ± 0.23%
SO ₃ :	2.77 ± 0.03%
MgO:	1.67 ± 0.23%
Fe ₂ O ₃ :	0.149 ± 0.005%
P ₂ O ₅ :	0.11 ± 0.05%
TiO ₂ :	0.09 ± 0.03%
K ₂ O:	0.08 ± 0.04%
SrO:	0.031 ± 0.001%
Mn ₂ O ₃ :	0.011 ± 0.006%
ZnO:	0.002 ± 0.001%

Alloys	
Today, 1:14 PM no name	
2024 (99% match)	
Al:	93.90 ± 0.07%
Cu:	3.526 ± 0.015%
Mg:	1.29 ± 0.15%
Mn:	0.469 ± 0.010%
Si:	0.33 ± 0.04%
Fe:	0.287 ± 0.008%
Zn:	0.085 ± 0.004%
Ti:	0.058 ± 0.016%
V:	0.013 ± 0.010%
Ni:	0.011 ± 0.003%
Cr:	0.009 ± 0.006%
Sn:	0.008 ± 0.006%
Ga:	0.007 ± 0.002%

Bluetooth

Wi-Fi

USB

Micro SD



TYPICAL APPLICATIONS



Analysis of Alloys and Scrap Sorting



Environmental Research (Soil and Sediment Analysis)



Analysis of Cement and Refractory Materials



Coating Thickness Measurement



Archaeological Research and Forensic Analysis



Precious Metal and Jewelry Analysis

TECHNICAL SPECIFICATIONS

X-ray Tube: Rh anode, 40 kV (W, Ag options)

Detector: Large-area SDD detector

Filters & Collimator: Automatic 5-position filter & fixed collimator

Detection Range: Mg – U

Dimensions & Weight: 242 × 230 × 78 mm; 1.4 kg

Ingress Protection: IP54

Connectivity: Optional Bluetooth & Wi-Fi

CCD Camera: Optional analysis area camera

ProSpector 2 LE is perfect for clients who require precision and flexibility for analyzing both light and heavy elements, making it ideal for specialized applications in environmental, industrial, and research fields.



Speed



Lightness



Accuracy



Stability

Elvatech Ltd. 50, Mashynobudivna str., Kyiv, 03067, Ukraine

Phone: (+1929) 243 99 06, (+38 063) 576 21 21, (+38 095) 576 21 21,

E-mail: office@elvatech.com

www.elvatech.com

